



**(43) International Publication Date**  
**21 July 2005 (21.07.2005)**

## PCT

**(10) International Publication Number**  
**WO 2005/065037 A2**

- (51) **International Patent Classification:** Not classified (74) **Agent:** REINHOLD COHN AND PARTNERS; P.O.B. 4060, 61040 Tel Aviv (IL).

(21) **International Application Number:** PCT/IL2005/000026 (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) **International Filing Date:** 9 January 2005 (09.01.2005)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:** 60/534,708 8 January 2004 (08.01.2004) US

(71) **Applicant** (*for all designated States except US*): YEDA RESEARCH AND DEVELOPMENT COMPANY LTD. [IL/IL]; At The Weizmann Institute of Science, P.O.Box 95, 76100 Rehovot (IL).

(72) **Inventors; and**

(75) **Inventors/Applicants** (*for US only*): FINKELSTEIN, Alexander [IL/IL]; C/31 Meonot Wolfson, Weizman Institute of Science, 76100 Rehovot (IL). KHODAS, Maxim [IL/IL]; 203/15 Herzl Street, 76274 Rehovot (IL). SHEHTER, Arcadi [IL/IL]; 39/9 Gordon Street, 76288 Rehovot (IL).


**Published:**  
— *without international search report and to be republished upon receipt of that report*

**Published:**

— without international search report and to be republished upon receipt of that report

*[Continued on next page]*

- (54) Title:** DEVICE AND METHOD FOR MANIPULATING DIRECTION OF MOTION OF CURRENT CARRIERS



- (57) Abstract:** A device and method for manipulating a direction of motion of current carriers are presented. The device comprises a structure containing a two-dimensional gas of current carriers configured to define at least one region of inhomogeneity which is characterized by a substantially varying value of at least one parameter from the following: a spin-orbit coupling constant, density of the spin carriers, and a mobility of the gas. The device may be configured and operable to perform spin manipulation of a flux of the spin carrying current carriers to provide at least one of the following types of deviation of said spin-carrying current carriers: spin dependent refraction, spin dependent reflection and spin dependent diffraction on desired deviation angles of a direction of motion of the spin-carrying current carriers being incident on said at least one region of inhomogeneity. The device may also be configured and operable to allow emission of the current carriers from a diffusive region at one side of the region of inhomogeneity to a ballistic region at the opposite side of the region of inhomogeneity to provide the current carriers propagation in multiple directions in the ballistic region with a wide angular range of these directions.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*